

Position	Qty.	Description
	1	<p><b>APG.50.92.3</b></p>  <p><b>Note! Product picture may differ from actual product</b></p> <p>Product No.: <a href="#">96005351</a> Submersible grinder pump</p> <p>Vertical single-stage cast iron submersible pump with integrated submersible 3-phase motor.</p> <p>The pump is fitted with carrying handle and is supplied with a 10 m mains cable.</p> <p>The pump is equipped with a hardened steel cutter system suitable for pumping wastewater and sewage in pressurised systems.</p> <p>The pump has a double shaft seal and an intermediate oil chamber pre-filled with non-toxic special oil.</p> <p>The motor is insulation class F and has long-life deep-groove greased-for-life ball bearings.</p> <p>The pump has DN 50 discharge port and is ready for installation on an auto-coupling system or can be supplied with ring stand for free-standing installation or portable use.</p> <p><b>Liquid:</b>  Pumped liquid: Any Newtonian liquid  Liquid temperature range: 0 .. 40 °C  Density: 998.2 kg/m³</p> <p><b>Technical:</b>  Type of impeller: CUTTER SYSTEM</p> <p><b>Materials:</b>  Pump housing: Cast iron  EN-JL1040</p>

Position	Qty.	Description
		<p>ASTM 35 B</p> <p>Impeller: Cast iron</p> <p>EN-JL1040</p> <p>ASTM 35 B</p> <p><b>Installation:</b></p> <p>Pump outlet: DN 50</p> <p>Maximum installation depth: 10 m</p> <p><b>Electrical data:</b></p> <p>Power input - P1: 11 kW</p> <p>Mains frequency: 50 Hz</p> <p>Rated voltage: 3 x 400 V</p> <p>Rated current: 19.1 A</p> <p>Cos phi - power factor: 0.81</p> <p>Rated speed: 2900 rpm</p> <p>Enclosure class (IEC 34-5): IP68</p> <p>Insulation class (IEC 85): F</p> <p>Length of cable: 10 m</p> <p>Type of cable plug: NONE</p> <p><b>Others:</b></p> <p>Net weight: 116 kg</p>