



IES-01 PN - klet - stropovi				
faze izgradnje	strop	št. pr.	ime	površina
1. FAZA	OPLESK	K 07	ARHIV	37,58
1. FAZA	OPLESK	K 06	HISNIK	43,34
1. FAZA	OPLESK	K 05	ELEKTRO PROSTOR	14,65
1. FAZA	OPLESK	K 04	STROJNICA	43,09
1. FAZA	OPLESK	K 03	STOPNICE	8,14
1. FAZA	OPLESK	K 02	HODNIK	17,09
1. FAZA	OPLESK	K 01	HODNIK	90,03
1. FAZA	PRTOTI PRAŠNI PREMAZ	K 08	DVIGALNI JAŠEK	4,70

Legenda stropov:

SS 01		Kovinski strop, kot npr.: Armstrong open cell lay-in CELLIO
SS 02		Mavčnkartonski spušen strop
SS 03		Spušen strop - lesena obloga, kot npr. Egger ProAcoustic Finest
SS 04		Samostojna jadra, kot npr.: Armstrong OPTIMA CANAPIY, mali pravokotnik
SS 05		Samostojna jadra, kot npr.: Armstrong OPTIMA CANAPIY, krog
SS 06		Spušeni bufferji kot npr.: Armstrong Buffles Soundscaoes blades CS401840 TWH

LEGENDA - KLET

K1		SEQUAL LINE starting module 17050 in 130W 840 W 110° 3164 mm DALI white (13833164001)	= 5,	Dolžina traja = 4420mm
		SEQUAL LINE central module 17050 in 130W 840 W 110° 3157 mm DALI white (13843164001)	= 60,	
		SEQUAL LINE end module 17050 in 130W 840 W 110° 3164 mm DALI white (13853484001)	= 5,	
K2		SEQUAL LINE starting module 12650 in 82W 840 W 110° 3164 mm DALI white (13833182001)	= 1,	Dolžina traja = 4420mm
		SEQUAL LINE central module 12650 in 82W 840 W 110° 3157 mm DALI white (13843182001)	= 12,	
		SEQUAL LINE end module 12650 in 82W 840 W 110° 3164 mm DALI white (13853482001)	= 1,	
K3		NITOR FLAT SOP 770 in 6W 840 IP44 white/white (148874820011)	= 33,	
K4		NITOR HE 2200 in 22W 840 IP44 (14840442001)	= 53,	
K5		KALIS ES WDI SOP 320x320 in 41+41W 840 2355 mm (13461484071)	= 5,	
K6		KALIS ES WDI SOP 240x240 in 31+31W 840 1695 mm (13461484051)	= 1,	
K7		KALIS ES WDI SOP 123x123 in 16+16W 840 855 mm (13461484021)	= 1,	
K8		5700 3250 in 27W 840 FO 1277mm IP68 (15711412000)	= 25,	
K9		MINUS C 6660 in 75W 840 2335 mm (13316408801)	= 1,	
svetilnika varnostne razsvetljave				
E	Beghelli tip Lungaluce	LED24W LP 1h, IP20, SE, LG-avtolest, asimetrična leča		
E1	Beghelli tip Diffusaluce	LED24W LP 1h, IP20, SE, LG-avtolest, difuzna leča		
E2	Beghelli tip Lungaluce	LED24W LP 1h, IP20, SE, LG-avtolest, okrogla leča		
E3	Beghelli tip Logica LED	LED11W 1h, IP44, SE, LG-avtolest,		
E4	Beghelli tip Indica 20 LED	LED2W 1h, IP20, SA, LG-avtolest, piktoqram enostranski		
E4A	Beghelli tip Indica 20 LED	LED2W 1h, IP20, SA, LG-avtolest, piktoqram dvostranski		
E5	Beghelli tip Indica 20 LED	LED2W 1h, IP20, SA, LG-avtolest, stenska, piktoqram enostranski		

SPREMEME



T +386 (0)22 228 29 88
F +386 (0)22 228 29 89
E info@styria.si

STYRIA ARHITEKTURA D.O.O.
CANARYNJA ULICA 6E / SI-2000 MARIBOR
WWW.STYRIA.SI



Občina
Miren-Kostanjevica

±0,00 = +4,97

OS Miren in postavitev nove telovadnice
OSNOVNA SKLADA MIREN, Miren 160
A: 222 - MIREN, p.p. št. 6203, 6207, 6208, 6209, 6210, 6214, 6216, 6218, 6242, 6244, 6245, 6601b, 6605, 6607, 6609,
670, 6712, 6714, 6716

Občina Miren-Kostanjevica
Miren 137, Miren - Slovenija

STROI

PZI - Projekt za izvedbo

Tloris strop - klet 1.F. ZAČASNO

SEPTEMBER 2018

01/18

David MISIC, Mag. Arch.

David MISIC, Mag. Arch.

Jermaj METEŽ, dipl.ing. grad.

Občina Miren-Kostanjevica, SI, 2018

merilo 1:50, 1:100, 1:1

3.2.1